

SKN72 Series

Total Transfer Security tape



PRODUCT DESCRIPTION

Traces of prints or patterns are totally transferred to substrates when the tape is removed. Excellent tamper evident performance.

APPLICATION

Suitable to seal paper packages and cardboard boxes.

TECHNICAL DATA

90°C Peel Adhesive for VOID:

0.20-0.98N/2,5cm

Total Thickness: 0.05-0.06mm

Initial Tack: < 10cm *PSTC-6 #14 ball*

Holding power:

1.0kg/2,5cm x 2,5cm :

>24 hrs *PSTC-7*

Holding power for temp. resist 60°C:

0.5kg/2,5cm x 2,5cm :

>24 hrs *PSTC-7*

STANDARD SIZE

50mm

LENGTH

30m ~ 500m

COLOR

Red, Blue, Brown

CARRIER:

PET

VOID TEMPERATURE

-10°C ~ +40°C;

RECOMMENDED

OPERATING TEMPERATURE

+10°C ~ +35°C

Relative humidity: 55% +/-10%

VOID MESSAGE

OPENED!

SHELF LIFE

1 year under normal condition. Avoid exposing to high humidity and direct sunlight.

HOW TO APPLY

When applying the tape the surfaces to be bonded should be dry, dust & grease free and thoroughly clean.

Avoid touching the exposed adhesive surface of the tape as this impairs the performance.

The adhesive used on these tapes are pressure sensitive, so always ensure sufficient pressure is applied to the tape evenly over the whole surface to ensure the best bonding results.

Multifoil products are produced under stringent manufacturing process and quality control conditions. The information and typical values provided are based upon research believed to be reliable and are provided without guarantee and do not constitute a warranty. Purchasers should determine the suitability of the products prior to its intended use.

Product liability – Terms of sale – article 8

Version May 2015

